

(1) **Scuff Tester.** ( Rub Proofness Tester )

Make "PackTest"

Digital Model

**Method of rubbing : Rotary.**

Blower-Free design.

**Confirming to PATRA / PIRA specification and BS-3110 standards.**

Desktop model with push button controls.

Non-contact type digital counter.

**Model : DX2**

Standard Model for normal applications with rubbing pressure of 2 psi (fixed)

Standard Rubbing Weight  $\pm$  2 psi.

With digital display of rubs

With Auto-Stop facility at user-defined counts.

With Digital display of speed (RPM)

**Model : HX2**

Heavy Duty Model for aggressive, variable rubbing pressure of up to 4 psi.

**Rubbing Pressures : 2, 2.5, 3, 3.5 & 4 psi.**

Standard Rubbing Weight : 2 psi.

Addon Rubbing Weight :  $\frac{1}{2}$  psi + 1 psi + 1 psi

**Free Accessories :**

- Sample Marking Templates (2 Inch and 4½ Inch Sample)
- Scissor
- GlueStick or similar quick drying adhesive.

**Optional Accessories :**

- **Precision Round Cutter Set.**

Set of 2 rotary cutters for Upper and Lower sample cutting.

Place on sample and rotate the knob  $\frac{1}{2}$  turn. You will get clean cut samples.

Also includes 2 (1+1) Foam Pad approx. 12" x 8".

**Extra Foam Pads available**

**Extra Blades (Set of 4 pcs) available**

Note : The larger round cutter can also be used for GSM testing as sample size is 100cm<sup>2</sup>.

**Utilities Required (To be supplied by the buyer) :**

- 1) Power Supply : 230 Volts AC at 50 Hz. (Fluctuation Free Power required)

**Optional Item (generally suggested for Pharmaceutical Companies only) :**

**IQQQ / Validation Documentation Set**

